

Asus H61M-C Socket 1155



Valutazione: Nessuna valutazione

Prezzo:

Modificatore prezzo variante:

Prezzo Base con IVA: 55,00 €

Prezzo di vendita scontato:

Prezzo di vendita: 55,00 €

[Fai una domanda su questo prodotto](#)

Produttore: [Asus](#)

Descrizione

- CPU
Intel® Socket 1155 for 3rd/2nd Generation Pentium®/Celeron® Processors
Supports Intel® 22 nm CPU
Supports Intel® 32 nm CPU
Supports Intel® Turbo Boost Technology 2.0
* The Intel® Turbo Boost Technology 2.0 support depends on the CPU types.
- Chipset
Intel® H61
- Memory
2 x DIMM, Max. 16GB, DDR3 2200(O.C.)/2133(O.C.)/2000(O.C.)/1866(O.C.)/1600/1333/1066 MHz Non-ECC, Un-buffered Memory
Dual Channel Memory Architecture
- Graphic
Integrated Graphics Processor
- Supports RGB with max. resolution 2048 x 1536 @ 75 Hz
Maximum shared memory of 1696 MB
- Expansion Slots
1 x PCIe 3.0/2.0 x16
1 x PCIe 2.0 x1
1 x PCI
- Storage
Intel® H61(B3) chipset :
4 x SATA 3Gb/s port(s), black

- LAN
Realtek® 8111F, 1 x Gigabit LAN Controller(s)
- Audio
Realtek® ALC887 8-Channel High Definition Audio CODEC *1
- USB Ports
Built-in Controller :
10 x USB 2.0 port(s) (4 at back panel, , 6 at mid-board)
- Special Features
ASUS Exclusive Features :
 - AI Suite II
 - Ai Charger
 - Anti-Surge
 - ASUS UEFI BIOS EZ Mode featuring friendly graphics user interface
 - Network iControl**ASUS Quiet Thermal Solution :**
 - ASUS Fan Xpert**ASUS EZ DIY :**
 - ASUS CrashFree BIOS 3
 - ASUS EZ Flash 2
 - ASUS MyLogo 2**100% All High-quality Conductive Polymer Capacitors**
- Back I/O Ports
1 x PS/2 keyboard (purple)
1 x PS/2 mouse (green)
1 x D-Sub
1 x LAN (RJ45) port(s)
4 x USB 2.0
1 x COM port(s)
1 x Parallel port(s)
3 x Audio jack(s)
- Internal I/O Ports
3 x USB 2.0 connector(s) support(s) additional 6 USB 2.0 port(s)
4 x SATA 3Gb/s connector(s)
1 x CPU Fan connector(s) (1 x 4 -pin)
1 x Chassis Fan connector(s) (1 x 4 -pin)
1 x S/PDIF out header(s)
1 x 24-pin EATX Power connector(s)
1 x 4-pin ATX 12V Power connector(s)
1 x Front panel connector(s)
1 x Front panel audio connector(s) (AAFP)
1 x Internal speaker connector(s)
1 x Clear CMOS jumper(s)
- Accessories
User's manual
I/O Shield
2 x SATA 3Gb/s cable(s)
- BIOS
64Mb Flash ROM, UEFI BIOS, PnP, DMI v2.0, WfM2.0, SMBIOS v2.7, ACPI v2.0a, SLP3.0, EUP-ready
- Manageability
WOL, PXE, PME Wake Up
- Support Disc
Drivers
ASUS Utilities
ASUS Update
Anti-Virus Software (OEM Version)
- Form Factor
uATX Form Factor
9 inch x 7 inch (22.6 cm x 17.8 cm)

- Note

*1:Use a chassis with HD audio module in the front panel to support an 8-channel audio output.

Recensioni

Nessuna recensione disponibile per questo prodotto.